

Paper Piecing steps:

- 1. Place the fabric for spot #1 on the wrong side of the paper, rights sides up. Secure with glue or pin.
- 2. Turn the paper over to the printed side, fold the paper back against the edge of your ruler (or postcard) along the line between spots #1 and #2 and trim the exposed fabric seam allowance to ¼".
- 3. Turn the paper over and line up the fabric piece for spot #2 right sides together with the cut edge of the fabric piece in spot #1. Check that fabric 2 will completely cover spot #2 including seam lines. Pin in place.
- 4. Turn the paper over to the printed side and sew with small stitches along the line between spots #1 and #2.
- 5. Press to the fabric in spot #2. Press on the fabric side; you can finger press or press with an iron.
- 6. Turn the paper over to the printed side, fold the paper back against the edge of your ruler along the line between spots #2 and #3 and trim the exposed fabric seam allowance to ¼".
- 7. Turn paper over and line up the fabric piece for spot #3 right sides together with the cut edge of the fabric piece in spot #2. Pin in place.
- 8. Turn the paper over and sew along the line between spots #2 and #3.
- 9. Press to the fabric in spot #3.
- 10. Repeat steps 6-9 until all pieces are added.

Paper Piecing steps:

- 1. Place the fabric for spot #1 on the wrong side of the paper, rights sides up. Secure with glue or pin.
- 2. Turn the paper over to the printed side, fold the paper back against the edge of your ruler (or postcard) along the line between spots #1 and #2 and trim the exposed fabric seam allowance to ½".
- 3. Turn the paper over and line up the fabric piece for spot #2 right sides together with the cut edge of the fabric piece in spot #1. Check that fabric 2 will completely cover spot #2 including seam lines. Pin in place.
- 4. Turn the paper over to the printed side and sew with small stitches along the line between spots #1 and #2.
- 5. Press to the fabric in spot #2. Press on the fabric side; you can finger press or press with an iron.
- 6. Turn the paper over to the printed side, fold the paper back against the edge of your ruler along the line between spots #2 and #3 and trim the exposed fabric seam allowance to ¼".
- 7. Turn paper over and line up the fabric piece for spot #3 right sides together with the cut edge of the fabric piece in spot #2. Pin in place.
- 8. Turn the paper over and sew along the line between spots #2 and #3.
- 9. Press to the fabric in spot #3.
- 10. Repeat steps 6-9 until all pieces are added.

www.katecollerandesigns.com

